

SK world

Aprile - Article Passport

Product Features

Applications	Upholstery and Drapery
Composition faceside	100% Polyester
Statistic Code	55121990
Dyeing method	Piece dyed
Available colours	24
Minimum workable width	300 CM
Roll length	30 M
GSM	285 GSM +/-5%
Backing/Finishing	--

Colours



Durability specifications

Test	Test Specification	Unit	Test result	
			WARP	WEFT
Colour Fastness To Rubbing	ISO 105-X12	Grade	4-5	
Colour Fastness To Light	UNE 40187 / BS 1006-B02	Grade	6	
Pilling	EN ISO/DIS 12945-1	Grade	5	
Abrasion Resistance	EN ISO 12947-2:1998	Martindale	70.000 Cycles	

Processing specifications

Test	Test Specification	Unit	Test result	
			WARP	WEFT
Breaking Strength	DIN EN ISO 13934-1:2014	Newton	46	63
Tearing Strength	ISO 13937-3:2000	mm	1.5	2

Cleaning specifications and Instructions

Test	Test Specification	Unit	Testresult	
			WARP	WEFT
Instructions				



Wash at or below 30°



Iron, low temp.



Dry clean, any solvent except trichloroethylene



Do not tumble dry



Do not bleach



SK world

Polígono Industrial C, Parcela B, Nave 9
 Prolongación C/Braçal del Roncador
 46800-Xàtiva-Valencia
 España
 +34 96 228 40 17