

SK world

Earth - Article Passport

Product Features

Applications	Upholstery and Drapery
Composition faceside	85% Polyester / 15% Cotton
Statistic Code	55121990
Dyeing method	Piece dyed
Available colours	19
Minimum workable width	140 CM
Roll length	35 40 M
GSM	510GS/M
Backing/Finishing	PCF FREE (NO PERFLUOROCARBON)

Colours



Durability specifications

Test	Test Specification	Unit	Test result	
			WARP	WEFT
Colour Fastness To Rubbing	ISO 105-D01	Grade	4-5	
Colour Fastness To Light	UNE 40187 / BS 1006-802	Grade	5	
Pilling	EN ISO/DIS 12945-1	Grade	4-5	
Abrasion Resistance	EN ISO 12947-2:1998	Martindale	80.000 Cycles	

Processing specifications

Test	Test Specification	Unit	Test result	
			WARP	WEFT
Breaking Strength	ISO 13937-3	Newton	-----	-----
Tearing Strength	BS 3320:1998 y BS 2543:1995	Newton	1100	750

Cleaning specifications and Instructions

Test	Test Specification	Unit	Test result	
			WARP	WEFT

Instructions



Wash at or below 30°



Do not bleach



Dry clean, any solvent except trichloroethylene



Iron, low temp.



Do not tumble dry



SK world

Poligono Industrial C, Parcela B, Nave 9
 Prolongación C/Braçal del Roncador
 46800-Xàtiva-Valencia
 España
 +34 96 228 40 17