

SK world

Hispania - Article Passport

Product characteristics

Applications	UPHOLSTERY
Composition faceside	98% Poly 2% Linen
Statistic Code	5407520000
Dyeing method	Piecedyed
Available colours	15
Minimum workable width	142 CM
Roll length	40 M
GSM	510GS/M
Backing/Finishing	Stabilized

Durability specifications

Test	Test Specification	Unit	Testresult	
			WARP	WEFT
Abrasion Resistance	ISO 12947-2:2016	Martindale	>40000	
Colour Fastness To Washing	ISO 105-C06:2010	Grade	4	
Colour Fastness To Light	ISO 105-B02:2014	Grade	4	
Pilling	ISO 12945-2:2000	Grade	3-4	

Processing specifications

Test	Test Specification	Unit	Testresult	
			WARP	WEFT
Seam Slippage	ISO 13936-2:2004	mm	2	3
Tensible Strenght	ISO 13934-1:2013	N	2000	2000

Cleaning specifications and Instructions

Test	Test Specification	Unit	Testresult	
			WARP	WEFT

Colors



Instructions



Wash at or
below 30°



Iron, low temp.



Do not
tumble dry



Do not
bleach

SK world

Polígono Industrial C, Parcela B, Nave 9
Prolongación C/Braçal del Roncador
46800-Xàtiva-Valencia
España
+34 96 228 40 17

